



# BLUE MAX® Liquid Rubber Waterproofer

*“Guaranteed to keep Water and Moisture out”*

## FAQs

1

### **WHAT WILL BLUE MAX ADHERE TO?**

Blue Max adheres to concrete, plywood, pressure treated wood, OSB, cedar, galvanized steel, EPDM, Drylok, and epoxy, eliminating the need to strip or prime the wall.

2

### **DOES BLUE MAX HAVE A WARRANTY?**

Yes, Blue Max has a 20 year Limited Warranty.

3

### **WHAT IS THE RATE OF COVERAGE?**

The product must be applied at the rate of 1 gal / 100 sq. ft. A minimum two coats recommended. Porous surfaces may require more product.

4

### **WHAT TOOLS ARE REQUIRED?**

Apply with a brush, roller, or commercial airless sprayer.

5

### **HOW LONG DO I HAVE TO WAIT BETWEEN COATS OF BLUE MAX?**

Typically, Blue Max will be dry to the touch and ready to recoat within 4-6 hours depending upon the temperature, humidity, exposure to sunlight, and air movement. You are always safe to wait 24 hours or more between coats of Blue Max.

6

### **CAN BLUE MAX BE TINTED?**

Blue Max is not tintable.

7

### **IS BLUE MAX MOLD AND MILDEW RESISTANT?**

Yes! Blue Max has been tested for 0% growth of mold and mildew.

8

### **DOES BLUE MAX REMAIN TACKY FOREVER?**

Blue Max is a highly adhesive elastomeric rubber and will remain slightly tacky even after it is fully cured.

9

### **WHAT DOES BLUE MAX SMELL LIKE AND HOW LONG WILL THE ODOR LAST?**

Blue Max has a slight ammonia odor which will dissipate within 24 hours.

**10****CAN I PAINT OVER BLUE MAX ON MY BASEMENT WALL?**

Yes, you can paint over Blue Max with a quality latex paint. Allow 48 hours for Blue Max to dry before painting over it.

**11****CAN I APPLY BLUE MAX TO EXTERIOR WALLS THAT ARE ABOVE-GRADE?**

Blue Max is UV sensitive and must be covered with a quality latex paint, siding, or shingles when applied to exterior above-grade surfaces.

**12****CAN BLUE MAX BE USED IN CISTERNS, POOLS, AND WATER FEATURES?**

Blue Max is formulated and designed to waterproof basements and foundations and is not currently marketed for cisterns, pools, and water features. It has been approved for use as a shower pan liner and is tile adhesive compatible.

**13****HOW LONG WILL IT LAST?**

When applied at the proper rate of application under the proper conditions in an environment free of UV exposure or mechanical abrasion Blue Max will last indefinitely.

**14****HOW DO I CLEANUP?**

Cleanup with soap and water.

## SELLING POINTS

**1**

**BLUE MAX WITHSTANDS 198 PSI PULL ADHESION TESTING ON HARDI-BOARD AND DOES NOT LIFT, BLISTER OR BUBBLE.**

**2**

**BLUE MAX WITHSTANDS 80 PSI PULL ADHESION TESTING ON CINDER BLOCK PREVENTING BLISTERING AND BUBBLING.**

**3**

**THE VAPOR PERMEABILITY OF BLUE MAX IS LOW! 0.49 PERMS**

**4**

**BLUE MAX CONTAINS LESS THAN 1 GRAM PER LITER OF VOLATILE ORGANIC COMPOUNDS MAKING IT ENVIRONMENTALLY FRIENDLY.**

**5**

**BLUE MAX IS SELF-SEALING AROUND NAILS AND FASTENERS.\***

\*Due to variables this feature is not Warranted.



**MADE IN THE USA**

BMXFAQ060520