



PHYSICAL PERFORMANCE PROPERTIES



AMES'® LIQUID GRANITE®

Ames® Liquid Granite® is an attractive granite-look coating that beautifies with a rich glow while it seals and protects. Liquid Granite is a beautiful granite-style coating that blocks out moisture and can even restore old surfaces through its strong adhesion. It is easy to apply and clean up, making it great for DIY projects. Great for use in bathrooms, patios, outdoor areas, and more.

Appearance (cured).....	Thick liquid	
Appearance (liquid).....	Clear with multicolor flecks	
PH.....	8.0-9.0	
Mildew Resistance.....	Excellent	
Weight.....		
Solvent.....	11.24	
Odor.....	Water	
Permeability.....	Slight odor	
Elongation.....	N/A	
Tensile Strength.....	N/A	
Humidity.....		
Boiling Point.....	50%	
Freezing Point.....	212°F	
Freeze/Thaw Stability Test.....	32°F	
Viscosity.....	ASTM D2243 Freeze Thaw Resistance of Water Borne coatings 3 cycles Pass	
Cure Time D5895.....	5000-6000 centipoise #6 spindle at 100 rpm Brookfield	
	At 40° - 80° F. 2 to 8 hours. allow 24 hours total curing. For best adhesion allow product to cure for up to 7 days.	
Toxicity	Non Toxic after curing	
Flash Point.....	ASTM D93 >200°C	
Coverage Rate.....	Approximately	100 square feet per gallon.
VOC Content.....	Less than 150 grams per liter	