



# TECHNICAL DATA SHEET



## AMES'® LIQUID GRANITE®

Ames'® Liquid Granite® is an attractive granite-look coating that beautifies with a rich glow while it seals and protects. Liquid Granite is a beautiful granite-style coating that blocks out moisture and can even restore old surfaces through its strong adhesion. It is easy to apply and clean up, making it great for DIY projects. Great for use in bathrooms, patios, outdoor areas, and more.

Appearance (cured).....	Thick liquid
Appearance (liquid).....	Clear with multicolor flecks
PH.....	8.0-9.0
Mildew Resistance.....	Excellent
Weight.....	11.24
Solvent.....	Water
Odor.....	Slight odor
Permeability.....	N/A
Elongation.....	N/A
Tensile Strength.....	N/A
Humidity.....	50%
Boiling Point.....	212°F
Freezing Point.....	32°F
Freeze/Thaw Stability Test.....	ASTM D2243 Freeze Thaw Resistance of Water Borne coatings 3 cycles Pass
Viscosity.....	5000-6000 centipoise #6 spindle at 100 rpm Brookfield
Cure Time D5895.....	At 40° - 80° F. 2 to 8 hours. allow 24 hours total curing. For best adhesion allow product to cure for up to 7 days.
Toxicity .....	Non Toxic after curing
Flash Point.....	ASTM D93 > 200°C
Coverage Rate.....	Approximately 70-100 square feet per 5 gallons.
VOC Content.....	Less than 150 grams per liter