



TECHNICAL DATA SHEET



AMES® SUPER PRIMER™

Ames® Super Primer™ is a unique, elastomeric plastic sealant, primer and adhesive for concrete, stucco, cement block, tile, brick, chimney, wood, metal and many hard-to-stick surfaces. It penetrates deeply into the surface to actually bind together the molecules of the surface it is being applied to. Rotting and deteriorating surfaces can be restored to a somewhat new condition and often the surface life can be extended for one or more years of usefulness.

Appearance (cured).....	Dries Clear
Appearance (liquid).....	Pearlescent White Liquid
Color.....	Clear
Mildew Resistance.....	Excellent
Weight.....	8.61 lbs/gal
Solvent.....	Water
Odor.....	Mild
Strength.....	
Viscosity.....	75 ± 25 cps, #2/100 rpm (Brookfield Model DV-1+)
PH as Shipped.....	9.0-10.0
Specific Gravity.....	
Bonding.....	
Humidity.....	Best applied when humidity level is below 50%
Freeze/Thaw Stability Test of Dried Materials.....	If frozen while in liquid form, may be damaged or solidify. Protect from freezing
Setting Time.....	Begins to dry in 10 minute and is usually dry within 2 hours. Heavier applications will require longer drying time. A slight tack is normal after drying.
Cure Time.....	Slight tack until cured.
Material Composition.....	
Toxicity.....	Non-toxic after curing. 1500° F. (estimated)
Flash Point.....	Class "A" ASTM E-108. over AC. ASTM E-84 zero smoke
Fire Rating.....	
Tukon Hardness (KHN).....	
Coverage Rate.....	100 to 200 square feet per gallon. Rough surfaces may require additional product and drying time.
Voc Content.....	Less than 1 gram per liter.

Formulas have been tested in accordance with ASTM E 108 E-108 Class "A" over AC. ASTM E-84 zero smoke, zero ignition. **Important:** Apply a small amount to ensure the product performs satisfactorily.

Ames Research Laboratories, Inc., 1891 16th St. SE Salem, OR 97302 USA

Toll-Free: 1-888-345-0809 | Phone: 503-588-3330 | Fax: 503-364-2380 | www.amesresearch.com | productservices@amesresearch.com